576 Optical Cable Specifications



Overview

The 576ZQ5-14700S53 from Corning Incorporated is a Fiber Optic Cable with Cable Diameter 20. 5 mm, Operating Wavelength 1310 nm, 1383 nm, 1550 nm, Attenuation 0. Providing up to 864 fibers in a compact design and long-term reliability in aerial, duct, and direct-buried applications. The FastAccess® jacket reduces access. Fiber OSP cable, LightScope ® ZWP Single Jacket All-Dielectric, High Fiber Count, 576 fiber, Gel-Filled, Stranded Loose Tube, Singlemode G. A1, Feet jacket marking, Black jacket color Finish making your selections or clear them to view relevant specifications. Get. Central Strength Member (CSM): glass fibres reinforced plastic rod (GRP). Stranding: loose tubes, SZ stranded around the CSM. Longitudinal Water Tightness:. OPTOKON Kable Co. is member of the OPTOKON GROUP0290-23/18 Specifications are to change without notice. Full dielectric cable for external. Corning UltraRibbon Plenum Dry Cables continue the innovative breakthrough in indoor cable technology with a new generation of high-fiber-count single tube cables. A specially formulated flame-retardant.

© 2026 AK OPTICAL SYSTEMS - All rights reserved

Article Content

Ribbon Fiber Cable

Product Number: FISR576RZ Indoor Flexible Ribbon OS2 576 Fibers OFNR Sub-Units 7.0 mm (144F) FX Indoor, Flexible Ribbon, OS2, 576 Fibers, OFNR, Sub-Units 7.0 mm (144F), Yellow Jacket

576ZQ5-14700S53

Get product specifications, Download the Datasheet, Request a Quote and get pricing for 576ZQ5-14700S53 on GoPhotonics.

Outdoor microduct optical fibre cable

These outdoor Sirocco HD microduct optical fibre cables are optimized for installation by blowing into microducts and protected microducts. Please contact your sales representative for ordering guides

Outdoor Multitube Cable 576F (ZC)

Specifications are to change without notice. The information in this document must not be copied or reproduced without the prior written permission of the OPTOKON Kable Co., Ltd., s.r.o.

Product Spec Sheet 576ZV8-14101-20

The cable maximizes the use of critical duct space and can easily fit in 1.25-in inner duct. A specially formulated flame-retardant jacket allows this cable to be used in indoor general purpose

Enbeam OS2 G.652.D Ribbon Fibre Cable Multi Loose Tube 576

Enbeam OS2 Singlemode G.652.D Ribbon Fibre Cable Multi Loose Tube 576 Core 9/125 HDPE Fca Black, part of a huge range of OS2 Fibre optic cables fully stocked at Mayflex. The Enbeam External

Product Spec Sheet 576EVF-14101-20

The smallest and lightest in the industry, these cables are designed to maximize the use of critical duct space with excellent installation results. The UV-resistant, flame-retardant jacket

Panduit F8ONM5E5EAAM100 576-Fiber Cable, OS2, Indoor /

Product Overview Singlemode (OS2) 576-fiber I/O LSZH Riser Euroclass Cca Female MTP to Female MTP Trunk, Method A, Standard IL, 100 meter.

SST-UltraRibbon Single-Tube, Gel-Free, Armored Cable 576 F, Bend ...

© 2026 AK OPTICAL SYSTEMS - All rights reserved

Corning SST-UltraRibbon gel-free cables continue the innovative breakthrough in outdoor cable technology by introducing a new generation of high-fiber-count gel-free cables. Providing high-fiber

Product Spec Sheet 576EVF-14101-20

576EVF-14101-20 Corning FREEDM UltraRibbon riser cables provide the ultimate solution for indoor/outdoor high-fiber-count applications. The smallest and lightest in the industry,

OM1 vs OM2 vs OM3 vs OM4 vs OM5 Multimode Fiber

Compare OM1, OM2, OM3, OM4, and OM5 multimode fiber specs, distances, bandwidth, and applications. Essential guide for data center fiber

OptiTect™ Advantage Fiber Distribution Hub 576-fiber Capaci

1. GENERAL The 576-fiber capacity Fiber Distribution Hub (FDH) functions as an interface between the telecommunication provider''s network and individual customer connections. The cabinet provides

FISR576RZ Technical Data Sheet

Fiber Specifications ... Cable Construction ... Outer Jacket Specifications ... Optical Characteristics ... Mechanical Characteristics ... Temperature Range ... Standards and Compliance

IEEE Std 576-2000, IEEE Recommended Practice for Installation ...

(This introduction is not a part of IEEE Std 576-2000, IEEE Recommended Practice for Installation, Termination, and Testing of Insulated Power Cable as Used in Industrial and Commercial

The FOA Reference For Fiber Optics

High Fiber Count Fiber Optic Cables As fiber optic communications systems are expanded to accommodate rapidly growing communications needs, thre has

FISR576RZ

Fiber Specifications Fiber Type: OS2, G.657.A1, G.652.D Fiber Diameter: 250 µm Fiber Count: 576 Fiber Color Coding: TIA-598-D

Product Spec Sheet 576EV4-14100D53

576EV4-14100D53 Corning SST-UltraRibbon gel-free cables continue the innovative breakthrough in outdoor cable technology by introducing a new generation of high-fiber-count gel-free cables.

SST-UltraRibbon™ 576 F Single-Tube, Gel-Free Cable

© 2026 AK OPTICAL SYSTEMS - All rights reserved

SST-UltraRibbon™ 576 F Single-Tube, Gel-Free Optical Fiber Cable Corning SST-UltraRibbon™ gel-free cables continue the innovative breakthrough in outdoor cable technology by introducing a new

Related Video Reference

This video was associated with the source search result. Verify technical details against current product documentation and project requirements.

Contact Us

Continue your research online:

Website: https://aboutkitchens.biz
Technical inquiry: https://aboutkitchens.biz/project-desk.html
North American project location: Research Triangle Park, North Carolina, United States

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 AK OPTICAL SYSTEMS - All rights reserved