
Distance between two cable trays



Overview

Discover the essential cable tray spacing requirements for safe and efficient installation. Learn key standards, horizontal and vertical spacing, and more.

Key Takeaways

The recommended distance between parallel cable trays is generally at least 0.6 meters, with specific clearances for power and signal trays and vertical spacing for maintenance and airflow.

Horizontal Spacing

When installing two cable trays in parallel at the same height, the minimum horizontal distance should be 0.6 meters to allow maintenance access, inspection, and proper heat dissipation, while preventing cables from touching and causing interference or short circuits (Apex Tray). For power and signal (control) trays, a horizontal separation of at least 0.5 meters is recommended to minimize electromagnetic interference (EMI). If the trays are shielded, this distance can be reduced to 0.3 meters (Apex Tray).

Industry standards also suggest a minimum of 300 mm (12 inches) between power and instrumentation trays to reduce EMI (Zero Instrument).

Vertical Spacing

For floor-mounted or stacked trays, the minimum vertical clearance is 150 mm to prevent obstruction, allow ventilation, and facilitate future installation of additional trays (Apex Tray). When trays are near ventilation ducts, a vertical clearance of at least 300 mm is recommended to ensure proper airflow and prevent overheating (Apex Tray).

© 2026 AK OPTICAL SYSTEMS - All rights reserved

Safety and Maintenance Considerations

Maintaining proper spacing ensures: Adequate airflow for heat dissipationSafe access for inspection and cable replacementReduced risk of EMI between power and signal cablesPrevention of water or moisture damage when near drainage systems (Apex Tray) Support and Span GuidelinesCable trays must also be supported according to manufacturer specifications and NEC requirements. Horizontal runs typically require supports every 4 to 6 feet, with a maximum of 5 feet for ladder-type trays to support cable weight and external loads (Zexin Electrical). Unsupported spans should not exceed 6 feet to prevent mechanical stress on cables (Electrical Trader).

Summary

Parallel trays: ≥ 0.6 m horizontalPower vs signal trays: ≥ 0.5 m (≥ 0.3 m if shielded)Vertical spacing: ≥ 150 mm (≥ 300 mm near ventilation)Support spacing: 4–6 ft for standard horizontal runs, max 5 ft for ladder trays Following these guidelines ensures safe, efficient, and code-compliant cable tray installations.

Article Content

Cable Tray Spacing Standards for Installation and Safety

Discover the essential cable tray spacing requirements for safe and efficient installation. Learn key standards, horizontal and vertical spacing, and more.

Cable Tray Support Spacing: Key Guidelines Explained

Explore the essential cable tray support spacing requirements for safe and efficient installations. Learn NEC guidelines for perforated, ladder, and wire

Safety Distance Between Cable Trays: What You Need

The safety distance between cable trays and systems such as ventilation and drainage is essential for maintaining a safe and efficient building.

Cable Tray Technical Guide A practical guide to product selection and ...

Cable tray length is selected based on the load to be supported, the distance between the supports (also referred to as the span), and handling and installation constraints.

Precautions for Cable Tray Installation

Under normal circumstances, the distance between the support arms of the cable tray should be about 1.5 m – 3 m, and should be verified according to specific conditions.

Cable Tray Installation Rules (NEC 392) – Electrical Trader

© 2026 AK OPTICAL SYSTEMS - All rights reserved

Generally, standard trays require supports every 6 to 10 feet, while heavy-duty, long-span trays can handle distances of up to 20 feet between supports. To determine the proper spacing,

Cable Support Distances

This provides distances for cables based on their diameter and cable type. Prysmian was instrumental in providing this information and an extract is provided in this document.

NEMA Standards Publication VE 2-2018

Do not use a cable tray as a walkway, ladder, or support for people; a cable tray is a mechanical support system for cables and raceways. Using cable trays as walkways can cause personal injury and can

Core Principles for Electrical and Instrumentation Cable Tray Layouts

Spacing Standards: Electrical (power) and instrumentation (signal/control) cable trays should maintain a minimum vertical and horizontal distance. Industry standards often recommend at least 300mm (12

Cable tray support spacing calculator

Not sure how far apart to space your cable tray supports? Use our free cable tray support spacing calculator to find the precise spacing.

B-Line series Cable Tray Design Considerations

Is your cable tray system optimized for safety, dependability, space and cost savings? Cable tray (or cable ladder) systems are a popular alternative to electrical conduit systems, as they have an

Typical Design Philosophy of Cable Trays for Power Plant

Vertical distance between adjacent cable trays, measured from the bottom of upper tray to the bottom of the lower tray, shall be at least 400 mm. To avoid damage during cable laying, cable

Cable Tray/Conduit Spacing

I have a standard from a particlar company on cable tray and conduit spacing based on the particular types of signals, voltage levels, etc. carried by the cables in the said cable

Factors to Consider for Cable Tray Spacing *Safety ...

Cable Tray Spacing When determining cable tray spacing, factors to consider include the tray''s load capacity, the weight of the cables, and the environment in which the tray will be installed.

© 2026 AK OPTICAL SYSTEMS - All rights reserved

Best Practice Guide to Cable Ladder and Cable Tray Systems

Cable ladder systems and cable tray systems are designed for use as supports for cables and not as enclosures giving full mechanical protection. They are not intended to be used as ladders, walk ways

NEMA Standards Publication VE 2-2018

The National Electrical Manufacturers Association (NEMA) Standards and guideline publications, of which the document herein is one, are developed through a voluntary development process. This

Cable tray separation | Automation & Control Engineering Forum

> 1) standard separation distance between power and signal cable trays installed vertically. > > 2)Also what is the priority of installing power cable tray and signal cable tray? I mean

CABLE TRAY SYSTEMS GUIDE

Steel Ladder System Hubbell''s NEXTFRAME® Ladder Tray is the effective and widely used cable runway that supports and delivers bundles of cable between cabinets, racks, and closets, along

Related Video Reference

This video was associated with the source search result. Verify technical details against current product documentation and project requirements.

Contact Us

Continue your research online:

Website: https://aboutkitchens.biz
Technical inquiry: https://aboutkitchens.biz/project-desk.html
North American project location: Research Triangle Park, North Carolina, United States

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 AK OPTICAL SYSTEMS - All rights reserved