# Optical power meter dB is negative



## Overview

Because the log of a number smaller than 1 is always negative, any power input (PmW) that is less than 1mW results in a negative dBm value.

## Article Content

Fiber Optic Series: Understanding dB and dBm values

When there''s loss in a fiber optic system, the measured power is less than the reference power, resulting in a negative logarithmic value and a negative dB

testing fiber optic power measurement

Because the log of a number smaller than 1 is always negative, any power input (PmW) that is less than 1mW results in a negative dBm value.

Understanding dBm vs mW in Fiber Optic Testing: A Complete Guide

In most fiber networks, the light signal is very weak — often weaker than a small flashlight. When this happens, the power meter shows a negative number in dBm. The signal has

dB vs dBm

Small signals are negative. For example, typical LED power sources have an output power of -20 dBm where as Laser and VCSEL sources for fiber optic testing have an output power of -10 dBm.

The FOA Reference For Fiber Optics

*© 2026 AK OPTICAL SYSTEMS - All rights reserved*

No question – loss means a more negative power reading in dB and a negative number in dB indicates loss.** But if you are a manufacturer of fiber optic test

dB vs dBm: Understanding the Difference in Fiber Optic Measurement

Understand the difference between dB vs dBm in fiber optic measurement. Learn how optical power, link loss, and optical testing work.

Introduction to Optical Fibers, dB, Attenuation and Measurements

To measure optical loss, you can use two units, namely, dBm and dB. While dBm is the actual power level represented in milliwatts, dB (decibel) is the difference between the powers. If the

Measurement Units

If we have loss in a fiber optic system, the measured power is less than the reference power, so the ratio of measured power to reference power is less than

dB vs dBm Explained for Fiber Optic Testing

Confused about dB and dBm in fiber optic testing? Learn the key differences and how to use each to measure power and signal loss accurately.

The Mysterious dB of Fiber Optics

Whenever tests are performed on fiber optic networks, the results are displayed on a meter readout in dB. Optical loss is measured in dB while optical power is measured in dBm. Loss is a negative

Fiber Optic Testing FAQs

How accurate are fiber optic power meters? All optical power meters which are calibrated to NIST (the US standards body) or any national standards lab will measure optical power to an uncertainty of

How to Measure Fiber Loss with Optical Power Meter

In optical fiber networks, the units of optical power are often expressed in milliwatts (mw) and decibel milliwatts (dbm). The relationship is: 1mw=0dbm,

When a Loss Is Positive: Fiber optic measurements

If you have read much on fiber optic testing, you have seen this equation defining dB, which, frankly, almost nobody understands: I am not going to get technical,

Practical tips for testing fiber optic power measurement

*© 2026 AK OPTICAL SYSTEMS - All rights reserved*

Calculating loss The basic formula used to calculate dB is: dB = 10 log (measured power / reference power). Whenever tests are performed on fiber optic networks, the results are displayed

The FOA Reference For Fiber Optics

Fiber Optic Measurement Units: "dB" and "dBm" Whenever tests are performed on fiber optic networks, the results are displayed on a power meter, OLTS or OTDR

testing fiber optic power measurement

Calculating loss The basic formula used to calculate dB is: dB = 10 log (measured power / reference power). Whenever tests are performed on fiber optic networks, the results are displayed on the meter

dB vs dBm

dBm (dB milliWatt) This is the signal strength or power level. 0 dBm is defined as 1 mW (milliWatt) of power into a power meter. Small signals are negative. For example, typical LED power sources have

What Is an Acceptable dBm for Fiber Internet?

The power received at the Optical Network Terminal (ONT) is virtually always less than one milliwatt, resulting in the received signal strength being expressed as a negative number, such as -20 dBm.

Related Video Reference

This video was associated with the source search result. Verify technical details against current product documentation and project requirements.

*© 2026 AK OPTICAL SYSTEMS - All rights reserved*

## Contact Us

Continue your research online:

Website: https://aboutkitchens.biz
Technical inquiry: https://aboutkitchens.biz/project-desk.html
North American project location: Research Triangle Park, North Carolina, United States

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 AK OPTICAL SYSTEMS - All rights reserved